



Chemicals

Gasola Soft-Set

Our top-selling general purpose PTFE sealant. Perfect for new work. Stays pliable in cold temperatures, non-hardening, non-separating, non-toxic. Not for use on oxygen. Temperature range: -100°F to 600°F. Pressure range: 10,000 psi sealing liquids; to 3,000 psi sealing gases. Sold in case quantities only.

Item No.	Description	List	Qty
SS01	1/8 oz tube Soft-Set Thread Sealant	1.11	100
SS02	2 oz tube	4.29	36
SS04	1/4 pint brush top can	12.16	24
SS08	1/2 pint	17.93	24
SS16	1 pint	29.89	12
SB32	1 quart	55.29	6
SS32	1 quart flat top cans	54.24	6



SS16

Gasola NT

Soft setting for applications requiring grit-free non-PTFE compounds. No fillers to contaminate gas lines. Use on pipes for potable water and food products. Not for use on oxygen. Temperature range: -50°F to 400°F. Pressure range: 6,000 psi sealing liquids; to 3,000 psi sealing gases. Sold in case quantities only.

Item No.	Description	List	Qty
NT02	2 oz tube Gasola-NT Thread Sealant	4.20	36
NT08	1/2 pint brush top can	17.00	24
NT16	1 pint	28.40	12



NT16

Gasola JC30 High Fill

For damaged, irregular, mis-cut and straight threads. Vegetable oil based, thick consistency. 10-15% more solids than conventional sealants. Forms a protective coating for valve stems and similar movable surfaces exposed to high humidity. Not for use on oxygen. Temperature range: -250°F to 500°F. Pressure range: 10,000 psi sealing liquids; to 2,000 psi sealing gases. Sold in case quantities only.

Item No.	Description	List	Qty
JC04	1/4 pt brush top can Gasola High-Fill Thread Sealant	17.09	24
JC16	1 pint	39.33	12



JC16

Gasola Hard Set

Hard setting, fast-drying, red varnish sealant for permanent joint. Excellent resistance to all petroleum products, refrigerants, freons, propane, kerosene, steam and more. Temperature range: -60°F to 350°F. Pressure range: 500 psi sealing face or butt joints; to 15,000 psi for threaded connections. Sold in case quantities only.

Item No.	Description	List	Qty
BT04	1/4 pt brush top can Gasola Hard Set	22.64	24
BT08	1/2 pint	34.16	24
BT16	1 pint	50.60	12
FT32	1 quart flat top	85.11	6



BT04



PB16-N

Gasoil PLS2

Lead-free, non-hardening, non-toxic opaque gray paste. Ideal for pneumatic and LPG applications. CSA and UL listed. Not for oxygen.

Temperature range: -100°F to 600°F. Pressure range: 10,000 psi sealing liquids; to 3,000 psi sealing gases. Sold in case quantities only.

Item No.	Description	List	Qty
PB02	2 oz tube PLS2 Premium Sealant	6.51	36
PB04	1/4 pint brush top can	20.00	24
PB16	1 pint	68.02	6



GH16

Gasoil 100

Ideal for use on systems with 100% methanol, ethanol, alcohol and highly corrosive chemicals. Soft setting. Not for use on oxygen, plastic pipe, or ethanol gasoline.

Temperature range: -50°F to 450°F. Pressure range: 10,000 psi sealing liquids; to 5,000 psi sealing gases. Sold in case quantities only.

Item No.	Description	List	Qty
GH04	1/4 pint brush top can Gasoil-100 soft-set	28.67	12
GH08	1/2 pint	40.80	12
GH16	1 pint	69.27	6



AS05

Fas-Seal anaerobic sealant

Forms a tough, insoluble, vibration-proof seal. Ideal for air conditioning lines, pneumatic lines, air compressor hoses and flared fittings. Not for use on oxygen.

Temperature range: -65°F to 375°F. Pressure range: 10,000 psi sealing liquids and gases. Sold in case quantities only.

Item No.	Description	List	Qty
AS05	Fas-Seal-ATS Non Shrinking 50ml tube	27.07	10
AS25	Fas-Seal-ATS Non Shrinking 250ml tube	70.62	10



GM12R

RTV Gasket Maker

Acetoxy cure RTV silicone sealant which provides a long-lasting flexible seal and excellent adhesion to most any surface. 7.25 oz Aerosol cans.

Temperature range: -80°F to 450°F. Sold in case quantities only.

Item No.	Description	List	Qty
GM12B	Silicone Gasket Maker Black	19.67	12
GM12R	Silicone Gasket Maker Red	19.67	12
GM12C	Silicone Gasket Maker Clear	19.67	12
GM12BL	Silicone Gasket Maker Blue	19.67	12

PTFE Rope

Ideal for valves and faucet packing. Sold in case quantities only.

Item No.	Description	List	Qty
ZJ11	3/32"od x 25ft coils Zip Joint PTFE Rope	23.40	6
ZJ12	3/32"od x 50ft	38.02	6
ZJ13	5/32"od x 25ft	46.49	6



ZJ11

Plumbers Grade PTFE Tape

Economy grade PTFE tape. Sold in case quantities only.

Item No.	Description	List	Qty
1901C	1/2" x 260" Roll Plumbers Grade PTFE Tape	0.42	100
1901D	1/2" x 520"	0.58	100
1901B	1/2" x 1296"	1.31	100
1901H	3/4" x 260" Roll Plumbers Grade PTFE Tape	0.58	140
1901E	3/4" x 520"	1.04	100
1901F	1" x 520" Roll Plumbers Grade PTFE Tape	1.76	50
1901G	1" x 1296"	3.13	140



1901D

Yellow PTFE Tape

Designed for chemical installations and sealing lines carrying natural gas, propane, butane and oil. CSA approved, UL listed thread sealant 131N, Meets MIL Spec MIL-AA-58092. Sold in cast quantities only.

Item No.	Description	List	Qty
YT70-24	1/2" x 260" rolls Yellow Thred Tape	5.53	24
YT70	1/2" x 260"	5.44	144
YT71	1/2" x 520"	9.44	100
YT75	1" x 520"	15.18	100



YT70

Pink PTFE Tape

Designed for sealing water and or steam lines. UL listed thread sealant 131N. Meets MIL Spec MIL-AA-58092. Sold in cast quantities only.

Item No.	Description	List	Qty
PT80-24	1/2" x 260" rolls Pink Thred Tape	5.38	24
PT80	1/2" x 260"	5.29	144



PT80

Green PTFE Tape

Designed for sealing oxygen based lines. UL listed thread sealant 131N. Meets MIL Spec MIL-AA-58092. Sold in cast quantities only.

Item No.	Description	List	Qty
GT90-24	1/2" x 260" roll Green Thred Tape	5.53	24
GT90	1/2" x 260"	5.44	144



GT90

Nickel Tape for Stainless Steel

Designed for use on stainless steel threads. Nickel base helps prevent seizing and galling. UL listed thread sealant 561R. Meets MIL Spec MIL-T-27730A. Sold in cast quantities only.

Item No.	Description	List	Qty
SA26	1/2" x 260" roll Nickel Coated Tape for SS Threads	8.98	40
SA60	1/2" x 600"	18.04	50
SA26-34	3/4" x 260"	11.89	40
SA260-1	1" x 260"	12.49	40
SA520-1	1' X 520"	24.98	40



SA26

Industrial Grade PTFE Tapes

UL listed thread sealant 561R (except standard density). Meets MIL spec MIL-T-27730A or AA-58092. Temperature range: - 400°F to 500°F. Pressure range up to 10,000 psi. Can be used for oxygen. Sold in case quantities only.



Item No.	Description	List	Qty
TT40	1/2" x 260" rolls High Density Industrial grade PTFE	5.00	144
TT41	1/2" x 520"	6.58	144
TT44	1/2" x 1296"	14.11	144
TT23	3/4" x 288"	6.89	24
TT33	3/4" x 576"	10.09	24

TT60	1/2" x 260" rolls Normal Density Industrial Grade PTFE	3.28	144
TT61	1/2" x 520"	5.00	144
TT53	3/4" x 260"	5.20	24
TT54	3/4" x 520"	7.69	24

ZT20	1/2" x 260" rolls Standard Density Tape	1.67	144
ZT21	1/2" x 500"	3.02	144
ZT12	3/4" x 250"	2.00	100
ZT13	3/4" x 500"	2.98	100
ZT51	1" x 520"	4.87	100
ZT60	2" x 260"	6.69	144

Anti-seizes

Speeds assembly, facilitates disassembly. Brush top cans for easy application. Non-hardening, non-dripping. Exceeds MIL spec MIL-A907D.

Temperature ranges, General Purpose -60°F to 1,000°F, Copper Base -60°F to 1,800°F, Nickel Base -60°F to 2,600°F. Sold in case quantities only.



Item No.	Description	List	Qty
TG04	1/4 pint brush top can General Purpose Anti-seize	11.40	24
TG08	1/2 pint	15.38	12
TG16	1 pint	22.04	12
CG04	1/4 pint brush top can Copper Based Anti-seize	12.47	24
CG08	1/2 pint	16.31	12
CG16	1 pint	22.91	12
NG04	1/4 pint brush top can Nickel Based Anti-seize	16.02	24
NG08	1/2 pint	22.64	12
NG16	1 pint	35.58	12

Leak Detector

Formulated for use on all types of pipe including CPVC. Non-toxic and Non-corrosive. Temperature range: 28°F to 180°F. Sold in case quantities only.



LS16

Item No.	Description	List	Qty
LT08	Gasoil Leak Tech Gold 8oz bottle	6.04	12
LS16	1 pint spray bottle	10.00	12
LT28	1 gallon	31.93	4
LT55	55 gallon drum	1101.29	1

Free All Deep Penetrating Oil

Free All Deep Penetrating Oil, penetrates rust, scale and corrosion instantly! The Rust Eater. Sold in case quantities only.

Item No.	Description	List	Qty
RE01	1oz aerosol Free All Penetrating Oil, The Rust Eater	2.87	25
RE06	6oz aerosol (old # FA06)	6.67	12
RE12	12oz aerosol (old # FA12)	10.53	12
FS16	1 pint spray bottle	13.96	12
FA28	1 gallon	55.09	4
FA55	55 gallon drum	2742.22	1



RE12

Lube-It-All

Lubricant contains molybdenumdisulphide for superior performance and is silicone free. Lube-It-All displaces 1,200 times its volume in water on surfaces and repels moisture to prevent corrosion. Temperature range: -300°F to 450°F. Sold in case quantities only.

Item No.	Description	List	Qty
LA01	1 oz aerosol Lube-It All	2.87	25
LA06	6 oz aerosol	6.36	12
LA12	12 oz aerosol	10.04	12



LA12

White Grease

White lithium grease. Will not run or drip on vertical surfaces. Use on chains, drives, hinges and other overhead surfaces.

Temperature range: -20°F to 275°F. Sold in case quantities only.

Item No.	Description	List	Qty
WG16	White Grease 14 oz aerosol	10.58	12



WG16

Expanding Foam

Insulates and seals cracks, gaps and openings to create an air tight bond. 3 to 1 expansion factor. Dries to the touch in 30 minutes, cures in four hours. UL surface burn test: Flame Spread:10, Smoke Development: 15, Burn Temperature: 240° F. Sold in case quantities only.

Item No.	Description	List	Qty
EF12	Expanding Foam 12oz aerosol	10.47	12



EF12

Stainless Steel Polish

Polishes stainless steel and chrome surfaces in one application. Removes tarnish, residues oxidation and also leaves a repellent coating. Safe for use in food preparation areas.

Sold in case quantity only.

Item No.	Description	List	Qty
SC16	Stainless Steel Polish 16oz aerosol	11.53	12



SC16



Chemicals



Cutting Oils

Light and dark cutting oils are both listed by the EPA and OSHA as non-carcinogenic. Sold in case quantities only.

Item No.	Description	List	Qty
WL28	1 gallon Light Cutting Oil	32.33	6
WL32	1 quart	16.93	12

WD28	1 gallon Dark Cutting Oil	29.84	6
WD32	1 quart	15.42	12



WD28



WD32

Water Finding Paste

Paste will turn yellow-green if it comes in contact with water. Sold in case quantities only.



WT25

Item No.	Description	List	Qty
WT25	Water Finding Paste 2.5oz tube	5.44	24
WF25	Water Finding Paste 3oz tub	6.20	24

Fas-Mark Cap and Cover Paint

Fas-Mark is a high solid, fast drying acrylic paint which can be applied to clean metal, wood, concrete, etc. Inverted spray can technology and a clean spray pattern means little or no over spray. Dries in 8 - 10 minutes. Offered in nine colors to mark and identify manhole and tank covers as noted below. VOC compliant. Aerosol 15oz cans. Sold in case quantities only.



Item No.	Description	List	Qty
FM15W	Fas-Mark White for unleaded gasoline	12.55	12
FM15BL	Fas-Mark Blue for mid-grade gasoline	12.55	12
FM15R	Fas-Mark Red for premium gasoline	12.55	12
FM15P	Fas-Mark Purple for racing fuel	12.55	12
FM15Y	Fas-Mark Yellow for diesel fuel	12.55	12
FM15G	Fas-Mark Green for heating oil	12.55	12
FM15BR	Fas-Mark Brown for kerosene	12.55	12
FM15O	Fas-Mark Orange for vapor recovery	12.55	12
FM15B	Fas-Mark Black	12.55	12

Tub-O Towels

Tub-O Towels are pre-moistened with our exclusive cleaning solution that removes grease, tar, ink, paint, permanent marker, PVC cement and other hard-to-remove soils. Tub-O Towels are gentle on hands and kill germs. They contains lanolin, aloe vera and vitamin E. The contractor size TW90, contains ninety 10" x 12" towels.

Item No.	Description	List	Qty
TW90	Tub-O Towels Tub contains 90 towels	27.67	6
TW90D	Tub-O Towels Floor Display, 30 tubs	776.70	1
TW40	Tub-O Towels Tub contains 40 towels	10.71	12
TW01-50	Tub-O Towels Counter Display Tub 50 foil pouches	49.00	1



TW90

Power Scrub

Formulated with pumice for the toughest grime. Clean hands with or without water. Sold in case quantities only.

Item No.	Description	List	Qty
PS15	Power Scrub Hand Cleaner 15 oz	6.18	12
PS28	Power Scrub Hand Cleaner 1 gallon pump	25.38	4
PS01-50	Power Scrub Hand Cleaner 1 oz pack	0.71	50



PS28 and PS15

Merchandiser

Item No.	Description	List	Qty
FM10	Floor Merchandiser	382.07	1



FM10



TW90D



Cable Ties White

Tough nylon cable ties have hundreds of uses. Sold by the bag only. Case quantity is the number of bags per case. Black cable ties are ultraviolet resistant.

Item No.	Description	List	Qty
CT04	4" White Cable Ties, 18 Tensile Strength, 100 per bag	1.13	10
CT06	6" White Cable Ties	3.11	10
CT08-18	8" White Cable Ties	4.37	10
CB04	4" Black Cable Ties	1.24	10
CB06	6" Black Cable Ties	3.98	10
CB08-18	8" Black Cable Ties	4.69	10

CT05	5" White Cable Ties, 40 Tensile Strength, 100 per bag	2.89	10
CT08	8" White Cable Ties	3.20	10
CB05	5" Black Cable Ties	4.37	10
CB08	8" Black Cable Ties	3.44	10

CT07	7" White Cable Ties, 50 Tensile Strength, 100 per bag	3.51	10
CT11	11" White Cable Ties	6.11	10
CT14	14" White Cable Ties	6.69	10
CT17	17" White Cable Ties	13.71	10
CB07	7" Black Cable Ties	3.78	10
CB11	11" Black Cable Ties	6.71	10
CB14	14" Black Cable Ties	7.35	10
CB17	17" Black Cable Ties	14.20	10



CT08-120	8" White Cable Ties, 120 Tensile Strength, 100 per bag	14.28	10
CT14-120	14" White Cable Ties	14.11	10
CT18	18" White Cable Ties	29.13	10
CB08-120	8" Black Cable Ties	13.40	10
CB14-120	14" Black Cable Ties	14.55	10
CB18	18" Black Cable Ties	40.04	10

CT24	24" White Cable Ties, 175 tensile Strength, 50 per bag	14.49	5
CT30	30" White Cable Ties	17.97	5
CT36	36" White Cable Ties	20.13	5
CT48	48" White Cable Ties	38.36	5
CB24	24" Black Cable Ties	15.93	5
CB36	36" Black Cable Ties	20.64	5
CB48	48" Black Cable Ties	39.35	5