



thread sealants

everseal thread sealant



PART NO.	DESCRIPTION	PKG.	LIST PRICE
JB08	1/2 pt. Brush	24	11.22
JB16	1 pt. Brush	12	17.82

- Soft-setting, non-toxic, gray PTFE paste sealant.
- For use on brass, copper, stainless steel, aluminum, black pipe, tin, galvanized, ABS, PVC plastics, nylon, polyethylene, polypropylene, polybutylene, and more.
- All purpose plumbing sealant for use on water, steam, compressed air, LPG, natural gas, propane, butane and more.
- Not for use on oxygen.
- Temperature Range: -100°F to 600°F (-74°C to 318°C).
Pressure Range: To 10,000 psi sealing liquids; to 3,000 psi sealing gases.
- Approved by CSA®, NSF® and UL.®

gasoila soft-set thread sealant



PART NO.	DESCRIPTION	PKG.	LIST PRICE
SS01	1/8 oz. Tube	100	.84
SS02	2 oz. Tube	36	3.20
SS04	1/4 pt. Brush	24	9.09
SS05	5 oz. Easy Seal Tube	24	12.13
SS08	1/2 pt. Brush	24	13.38
SS16	1 pt. Brush	12	22.31
SB32	1 qt. Brush	6	41.27
SS32	1 qt. Flat Top	6	40.47
SS28	1 Gallon	4	150.04
SSDC2	1/2 pt. Display Carton	1	11.11

- Soft-setting, non-toxic, PTFE paste sealant..
- For use on brass, copper, stainless steel, aluminum, black pipe, tin, galvanized, ABS, PVC plastics, nylon, polyethylene, polypropylene, polybutylene, and more.
- Excellent resistance to gasoline (up to 20% alcohol and petroleum blends), petroleum solvents, kerosene, diesel oil, propane, butane, LPG, cutting oils, ammonia, aliphatic solvents, acids, steam, potable water, compressed air and more.
- Not for use on oxygen.
- Temperature Range: -100°F to 600°F (-74°C to 318°C).
Pressure Range: To 10,000 psi sealing liquids; to 3,000 psi sealing gases.
- Approved by CSA®, NSF® and UL.®

thread sealants

gasoila-nt thread sealant

PART NO.	DESCRIPTION	PKG.	LIST PRICE
NT02	2 oz. Tube	36	3.16
NT08	1/2 pt. Brush	24	12.71
NT16	1 pt. Brush	12	21.18



- Blue, non-PTFE, grit-free sealant.
- Can be used on all metals, as well as most plastics.
- Recommended for use with valves, fittings, hoses, nozzles, motors, housings, gaskets, compressors, casings, etc.
- Can be used with food and potable water.
- Not for use with oxygen.
- Temperature Range: -50°F to 400°F (-45°C to 204°C).
- Pressure Range: To 6,000 psi sealing liquids; 3,000 psi sealing gases.
- NSF® Approved

gasoila high-fill thread sealant

PART NO.	DESCRIPTION	PKG.	LIST PRICE
JC04	1/4 pt. Brush	24	13.13
JC16	1 pt. Brush	12	30.24



- High viscosity, heavy-duty, non-toxic PTFE thread sealant.
- Ideal for use on used, damaged, irregular or new threads.
- Provides excellent chemical resistance in use with water, steam, corrosives, acids, petroleum products, hydraulic fluids, jet fuel, CNG, LP and natural gas.
- Can be used with Freon 22, aromatic fluids, and food products.
- Not for use with oxygen.
- Temperature Range: -250°F to 500°F (-157°C to 260°C).
- Pressure Range: To 2,000 psi for gases; 10,000 psi for liquids



free all deep penetrating oil



PART NO.	DESCRIPTION	PKG.	LIST PRICE
FA01	1 oz. Aerosol	12	4.51
FA06	6 oz. Aerosol	12	5.11
FA12	12 oz. Aerosol	12	8.11
FA16	1 pt. Spout	12	10.56
FS16	1 pt. Spray	12	11.27
FA28	1 gallon	6	42.38
FA55	55 gal. Drum	1	1382.98
FADC	12 oz. Aerosol Display	1	6.67

- Penetrates rust, scale, and corrosion to free parts and assemblies INSTANTLY!
- Loosens red and white lead, tar, grease, carbon, and graphite deposits.
- Specially formulated rust eating agent is ideal for plumbing, automotive, marine and general industrial applications.
- Will free up all threaded pipe connections, rusted machine screws, bolts, nuts, clamps for mufflers and tail pipes, pillow blocks, universal joints, locks, etc.
- Contains NO silicones.
- Our eye-catching, 4 color reusable counter display arrives pre-assembled, takes up minimal space, and holds 12 - 12oz. cans.

lube-it-all deep lubricating oil



PART NO.	DESCRIPTION	PKG.	LIST PRICE
LA06	6oz. Aerosol	12	5.11
LA12	12 oz. Aerosol	12	8.11

- Contains Molybdenumdisulphide for superior lubricating performance!
- Forms a thin, dry lubricant coating to reduce friction.
- Displaces 1200 times its volume in water on surfaces and repels moisture to prevent corrosion.
- Does not conduct electricity, allowing use on switches and solenoids.
- Temperature Range: -300°F to 450°F (-184°C to 232°C).

ptfe tapes

industrial grade ptfe tapes

high-density

PART NO.	DESCRIPTION	PKG.	LIST PRICE
TT23	3/4" x 288"	24	6.13
TT33	3/4" x 576"	24	8.98
TT40	1/2" x 260"	144	4.44
TT41	1/2" x 520"	144	5.87



normal-density

PART NO.	DESCRIPTION	PKG.	LIST PRICE
TT53	3/4" x 260"	24	4.64
TT54	3/4" x 520"	24	6.84
TT60	1/2" x 260"	144	2.91
TT61	1/2" x 520"	144	4.44

standard-density

PART NO.	DESCRIPTION	PKG.	LIST PRICE
ZT12	3/4" x 250"	100	1.78
ZT13	3/4" x 500"	100	2.64
ZT20	1/2" x 260"	144	1.49
ZT21	1/2" x 520"	144	2.69

- All are U.S.A. made with 100% Virgin PTFE.
- Can be used on oxygen.
- UL® Listed thread sealant 651R (except Standard Density Zip® Tape).
- Meets Mil Spec MIL-T-27730A (except Standard Density Zip® Tape).
- Temperature Range: -400°F to 500°F (-240°C to 260° C).
- Pressure Range: To 10,000 psi.

economy ptfe tape

PART NO.	DESCRIPTION	PKG.	LIST PRICE
1901D	1/2" x 520"	100	.42
1901E	3/4" x 520"	100	.80
1901F	1" x 520"	50	1.33



- Meets Mil Spec MIL-T-27730A



yellow zip® tape

- Designed for sealing lines carrying natural gas, propane, butane, as well as oil and chemical installations.
- Density: 1.3 sg.
- Temperature Range: -400°F to 500°F (-240°C to 260°C).
- CSA® approved. UL® Listed thread sealant 131N.
- Meets MIL Spec MIL-AA-58092.

PART NO.	DESCRIPTION	PKG.	LIST PRICE
YT70-24	1/2" x 260"	24	4.93
YT70	1/2" x 260"	144	4.84

pink zip® tape

- Designed for sealing water and/or steam lines.
- Use on all types of pipe.
- Density: 1.3 sg
- Temperature Range: -400°F to 500°F (-240°C to 260°C).
- UL® Listed thread sealant 131N.
- Meets MIL Spec MIL-AA-58092.

PART NO.	DESCRIPTION	PKG.	LIST PRICE
PT80-24	1/2" x 260"	24	4.78
PT80	1/2" x 260"	144	4.69



stainless steel zip® tape

- Designed for use on difficult service conditions associated with stainless steel, aluminum, and brass threaded connections.
- Pure nickel base helps prevent seizing and galling.
- Temperature Range: -450°F to 550°F (-252°C to 290°C).
- UL® Listed thread sealant 561R.
- Meets MIL Spec MIL-T-27730A.

PART NO.	DESCRIPTION	PKG.	LIST PRICE
SA26	1/2" x 260"	40	8.00

hand cleaners

tub o' towels power cleaner

PART NO.	DESCRIPTION	PKG.	LIST PRICE
TW90	90 Wipes per Canister	6 Canisters	24.58

- Heavy-duty, pre-moistened disposable towels.
- Removes grease, sealants, adhesives, oil and more from hands and tools.
- Each re-sealable, pop-open tub contains 90 multi-purpose towels



power scrub hand cleaner

PART NO.	DESCRIPTION	PKG.	LIST PRICE
PS15	15 oz. Can	12	4.56
PS28	1 ga. Pump	4	21.73



- Cleans hands with or without water.
- Contains pumice to remove tough grime, grease, tar, oils and more.
- Balanced pH prevents burning of cuts and scrapes.
- Contains a blend of essential oils plus lanolin and aloe to leave hands smooth and comfortable.



specialty chemicals

gasoila leak-tech gold



PART NO.	DESCRIPTION	PKG.	LIST PRICE
LS16	1pt. spray bottle	12	8.49
LT28	1 gallon	4	27.07
LT55	55 gallon drum	1	808.24

- Gasoila Leak-Tech Gold is specifically engineered for use on gas lines, gas cylinders, refrigeration condensers, water lines, air lines, air pumps, or any other system carrying gas. It can be used on all types of piping including FlowGuard Gold® CPVC systems.
- Use on all types of plastic and metal piping.
- Non-toxic, non-corrosive.
- Temperature Range: -5°F (-20°C) to 180°F (82°C).
- Not for use on oxygen systems.

FlowGuard Gold® is a registered trademark of Noveon, Inc.



rtv silicone gasket maker



PART NO.	DESCRIPTION	PKG.	LIST PRICE
GM12R	7.25 oz. (red)	12	24.07
GM12B	7.25 oz. (black)	12	24.07
GM12C	7.25 oz. (clear)	12	24.07

- Provides a long-lasting flexible seal and excellent adhesion to most surfaces, such as glass, wood, metal, plastic, ceramic, tile, fabric, vinyl, and many other surfaces.
- Adhesive Sealant – 100% Silicone Rubber.
- Easy to use dispenser – No caulk gun needed.
- Uniform bead every time.

super-set stainless putty



PART NO.	DESCRIPTION	PKG.	LIST PRICE
SP14	14 oz. tub	24	2.09

specialty chemicals

bundle buddies nylon cable ties

clear

PART NO.	DESCRIPTION	PKG.	LIST PRICE
CT07	7"	10 Bags of 100	6.58
CT11	11"	10 Bags of 100	13.29
CT14	14"	10 Bags of 100	16.04
CT24	24"	5 Bags of 50	26.73
CT36	36"	5 Bags of 50	29.93
CT48	48"	5 Bags of 50	44.20



uv-nylon (black)

PART NO.	DESCRIPTION	PKG.	LIST PRICE
CB07	7"	10 Bags of 100	7.36
CB11	11"	10 Bags of 100	14.93
CB14	14"	10 Bags of 100	19.02
CB24	24"	5 Bags of 50	29.42
CB36	36"	5 Bags of 50	34.77

- Tough nylon cable ties have thousands of uses.
- UL recognized and MIL Spec approved.
- Continuous locking threads let you adjust to the exact length needed.
- UV (black) cable ties are ultraviolet resistant for prolonged life.
- 7", 11", and 14" come in 10 Bags of 100
- 24", 36", and 45" come in 5 Bags of 50

expanding foam

PART NO.	DESCRIPTION	PKG.	LIST PRICE
EF12	12 oz. Aerosol Can	12	8.87



- Insulates and seals around ducts, pipes, air conditioning units, heating equipment, vents and more.
- Cured product can be trimmed, sanded and painted.
- Foam cures to the touch in 45 minutes, and sets in 24 hours.
- UL® Classified.



specialty chemicals

stainless steel polish



PART NO.	DESCRIPTION	PKG.	LIST PRICE
SC16	16 oz. Aerosol Can	12	8.87

- Polishes stainless steel and chrome surfaces in one application.
- Acceptable for use in federally inspected meat and poultry plants.
- Removes tarnish, residues, and oxidation and leaves a repellent coating.
- Ideal for use in restaurants, cafeterias, hospitals, and marine applications.

epoxy putty



PART NO.	DESCRIPTION	PKG.	LIST PRICE
EP04	4 oz. tube	24	9.07

- Works like putty, & hardens like steel in less than 8 minutes
- Adheres to plastics, metals, and fibrous materials.
- Product can be drilled, sanded, painted, and applied under water.
- Temperature Range: -100°F to 600°F (-74°C to 318°C)
- Pressure Rating: 300 psi.