



**Chemicals**

## Gasoil® Soft-Set

Our top-selling general purpose PTFE sealant. Perfect for new work. Stays pliable in cold temperatures, non-hardening, non-separating, non-toxic. Not for use on oxygen.

Temperature range: -100°F to 600°F. Pressure range: 10,000 psi sealing liquids; to 3,000 psi sealing gases. Sold in case quantities only.

Item #	Description	Qty
SS01	1/8 oz. tube Gasoil® Soft-Set Thread Sealant	100
SS02	2 oz. tube	24
SS04	1/4 pint brush top can	24
SS08	1/2 pint	24
SS16	1 pint	12
SB32	1 quart	6
SS32	1 quart flat top cans	6



SS16

## Gasoil® NT

Soft setting for applications requiring grit-free non-PTFE compounds. No fillers to contaminate gas lines. Use on pipes for potable water and food products. Not for use on oxygen.

Temperature range: -50°F to 400°F. Pressure range: 6,000 psi sealing liquids; to 3,000 psi sealing gases. Sold in case quantities only.

NT08-N	1/2 pint brush top can Gasoil®-NT Thread Sealant	24
NT16-N	1 pint	12



NT16

## Gasoil® JC30 High Fill

For damaged, irregular, mis-cut and straight threads. Vegetable oil based, thick consistency. 10-15% more solids than conventional sealants. Forms a protective coating for valve stems and similar movable surfaces exposed to high humidity. Not for use on oxygen.

Temperature range: -250°F to 500°F. Pressure range: 10,000 psi sealing liquids; to 2,000 psi sealing gases. Sold in case quantities only.

JC04	1/4 pt brush top can Gasoil® High-Fill Thread Sealant	24
JC16	1 pint	12



JC16

## Gasoil® Hard Set

Hard setting, fast-drying, red varnish sealant for permanent joint. Excellent resistance to all petroleum products, refrigerants, freons, propane, kerosene, steam and more.

Temperature range: -60°F to 350°F. Pressure range: 500 psi sealing face or butt joints; to 15,000 psi for threaded connections. Sold in case quantities only.

BT04	1/4 pt brush top can Gasoil® Hard Set	24
BT08	1/2 pint	24
BT16	1 pint	12
FT32	1 quart flat top	6



BT04

## PLS2®

Lead-free, non-hardening, non-toxic opaque gray paste. Ideal for pneumatic and LPG applications. CSA and UL listed. Not for oxygen.

Temperature range: -100°F to 600°F. Pressure range: 10,000 psi sealing liquids; to 3,000 psi sealing gases. Sold in case quantities only.

PB04-N	1/4 pint brush top can	24
PB16-N	1 pint	6



PB16-N



Chemicals



GH16

### Gasoila® 100

Ideal for use on systems with 100% methanol, ethanol, alcohol and highly corrosive chemicals. Soft setting.

Not for use on oxygen, plastic pipe, or ethanol gasoline.

Temperature range: -50°F to 450°F. Pressure range: 10,000 psi sealing liquids; to 5,000 psi sealing gases. Sold in case quantities only.

Item #	Description	Qty
GH04	1/4 pint brush top can Gasoila® -100 soft-set	12
GH08	1/2 pint	12
GH16	1 pint	6



AS05

### Fas-Seal ATS® Anaerobic Sealant with PTFE

Forms a tough, insoluble, vibration-proof seal. Ideal for air conditioning lines, pneumatic lines, air compressor hoses and flared fittings.

Non-shrinking. Not for use on oxygen.

Temperature range: -65°F to 375°F. Pressure range: 10,000 psi sealing liquids and gases. Sold in case quantities only.

AS05	50 ml tube Fas-Seal-ATS®	10
AS25	250 ml tube	10



LS16



LT08

### Leak-Tech Gold, Leak Detector

Formulated for use on all types of pipe including CPVC.

Non-toxic and Non-corrosive.

Temperature range: -10°F to 350°F. Sold in case quantities only.

LT08	8 oz. bottle Gasoila® Leak Tech Gold	12
LS16	1 pint pump spray bottle	12
LT28	1 gallon	4
LT55	55 gallon drum	1

### Thred Gard Anti-Seizes Compounds

Speeds assembly, facilitates disassembly. Brush top cans for easy application.

Non-hardening, non-drippng. Exceeds MIL spec MIL-A907D.

Temperature ranges,

General Purpose -60°F to 1,000°F

Copper Base -60°F to 1,800°F

Nickel Base -60°F to 2,600°F Sold in case quantities only.



NG16



TG16

TG04	1/4 lbs. brush top can General Purpose Anti-seize	24
TG08	1/2 lbs.	12
TG16	1 lbs.	12
CG04	1/4 lbs. brush top can Copper Based Anti-seize	24
CG08	1/2 lbs.	12
CG16	1 lbs.	12
NG04	1/4 lbs. brush top can Nickel Based Anti-seize	24
NG08	1/2 lbs.	12
NG16	1 lbs.	12

## Free All® Deep Penetrating Oil

Free All® Deep Penetrating Oil, penetrates rust, scale and corrosion instantly! The Rust Eater. Sold in case quantities only.

Item #	Description	Qty
RE01	1 oz. aerosol Free All® Penetrating Oil, The Rust Eater	12
RE06	6 oz. aerosol (old # FA06)	12
RE12	11 oz. aerosol (old # FA12)	12
FS16	1 pint spray bottle	12
FA28	1 gallon	4
FA55	55 gallon drum	1



RE12

## Lube-It-All®

Lubricant contains molybdenumdisulphide for superior performance and is silicone free. Lube-It-All® displaces 1,200 times its volume in water on surfaces and repels moisture to prevent corrosion.

Temperature range: -300°F to 450°F. Sold in case quantities only.

LA01	1 oz. aerosol Lube-It All®	25
LA06	6 oz. aerosol	12
LA12	11 oz. aerosol	12



LA12

## White Grease

White lithium grease. Will not run or drip on vertical surfaces. Use on chains, drives, hinges and other overhead surfaces.

Temperature range: -20°F to 275°F. Sold in case quantities only.

WG16	14 oz. aerosol White Grease	12
------	-----------------------------	----



WG16

## Expanding Foam

Insulates and seals cracks, gaps and openings to create an air tight bond. 3 to 1 expansion factor. Dries to the touch in 30 minutes, cures in four hours. UL surface burn test: Flame Spread:10, Smoke Development: 15, Burn Temperature: 240° F. Sold in case quantities only.

EF12	12 oz. aerosol Expanding Foam	12
------	-------------------------------	----



EF12

## Stainless Steel Polish

Polishes stainless steel and chrome surfaces in one application. Removes tarnish, residues oxidation and also leaves a repellent coating. Safe for use in food preparation areas. Sold in case quantity only.

SC16	16 oz. aerosol Stainless Steel Polish	12
------	---------------------------------------	----



SC16

## Fas-Mark® Cap and Cover Paint

Fas-Mark® is a high solid, fast drying acrylic paint which can be applied to clean metal, wood, concrete, etc. Inverted spray can technology and a clean spray pattern means little or no over spray. Dries in 8 - 10 minutes. Offered in nine colors to mark and identify manhole and tank covers as noted below. VOC compliant. Aerosol 15 oz. cans. Sold by case.

FM15W	White for unleaded gasoline	12
FM15BL	Blue for mid-grade gasoline	12
FM15R	Red for premium gasoline	12
FM15P	Purple for racing fuel	12
FM15Y	Yellow for diesel fuel	12
FM15G	Green for heating oil	12
FM15BR	Brown for kerosene	12
FM15O	Orange for vapor recovery	12
FM15B	Black	12



Chemicals



ZJ11

### PTFE Rope

Item #	Description	Qty
ZJ11	Zip Joint PTFE Rope 3/32" od x 25 ft coils	6
ZJ12	3/32" od x 50 ft	6
ZJ13	5/32" od x 25 ft	6

### Plumbers Grade PTFE Tape

Economy grade PTFE tape. Sold by case.

1901C	1/2" x 260"	100
1901D	1/2" x 520"	100
1901B	1/2" x 1296"	100
1901H	3/4" x 260"	140
1901E	3/4" x 520"	100
1901F	1" x 520"	50
1901G	1" x 1296"	140



1901D

### Yellow PTFE Tape

Designed for chemical installations and sealing lines carrying natural gas, propane, butane and oil. CSA approved, UL listed thread sealant 131N, Meets MIL Spec MIL-AA-58092.

YT70-24	1/2" x 260" rolls	24
YT70	1/2" x 260"	144
YT71	1/2" x 520"	100
YT75	1" x 520"	100



YT70

### Pink PTFE Tape

Designed for sealing water and or steam lines. UL listed thread sealant 131N. Meets MIL Spec MIL-AA-58092.

PT80-24	1/2" x 260" rolls	24
PT80	1/2" x 260"	144



PT80

### Green PTFE Tape

Designed for sealing oxygen based lines. UL listed thread sealant 131N. Meets MIL Spec MIL-AA-58092.

GT90-24	1/2" x 260" rolls	24
GT90	1/2" x 260"	144



GT90

### Nickel Tape - Stainless Steel

Designed for stainless steel threads. Nickel base prevents seizing and galling. UL listed thread sealant 561R. Meets MIL Spec MIL-T-27730A. Sold by case only.

SA26	1/2" x 260" rolls	40
SA60	1/2" x 600"	50
SA26-34	3/4" x 260"	40
SA260-1	1" x 260"	40
SA520-1	1" X 520"	40



SA26

### Industrial Grade PTFE Tapes

UL listed thread sealant 561R (except standard density). Meets MIL spec MIL-T-27730A or AA-58092. Temperature range: - 400°F to 500°F. Pressure range up to 10,000 psi. Can be used for oxygen. Sold in case quantities only.

Item #	Description	Qty
TT40	High Density Industrial 1/2" x 260" rolls	144
TT41	1/2" x 520"	144
TT44	1/2" x 1296"	144
TT23	3/4" x 288"	24
TT33	3/4" x 576"	24



TT60	Normal Density Industrial 1/2" x 260" rolls	144
TT61	1/2" x 520"	144
TT53	3/4" x 260"	24
TT54	3/4" x 520"	24



ZT20	Standard Density Tape 1/2" x 260" rolls	144
ZT21	1/2" x 520"	144
ZT12	3/4" x 250"	100
ZT13	3/4" x 500"	100
ZT51	1" x 520"	100
ZT60	2" x 260"	144



### Water Finding Paste

Paste will turn yellow-green if it comes in contact with water. Sold by case only.

WT25	2.5 oz. tube	24
WF25	2.5 oz. tub	24
AP02	All Purpose 2 oz. tube	24



WT25

### Cutting Oils

Light and dark cutting oils are both listed by the EPA and OSHA as non-carcinogenic. Sold in case quantities only.

WL28	Light Cutting Oil 1 gallon	4
WL32	1 quart	12



WD32



WD28

WD28	Dark Cutting Oil 1 gallon	4
WD32	1 quart	12

### Power Scrub

Formulated with pumice for the toughest grime.

PS15	Power Scrub Hand Cleaner 15 oz	12
PS28	Power Scrub Hand Cleaner 1 gallon pump	4



PS28 and PS15

## Tub O' Towels®

Tub O' Towels® are pre-moistened with our exclusive 9 different cleaning solutions that removes grease, tar, ink, paint, permanent marker, PVC cement and other hard-to-remove soils. Tub O' Towels® are gentle on hands as they contain lanolin, aloe vera and vitamin E.

TW90 towels are 10" x 12" and TW40 towels are 7" x 10".

Item #	Description	Qty
TW40	TW40 contains 40 towels	12
TW90	TW90 contains 90 towels	6
TW40-CD	TW40 Counter Display (12 per display)	1 display
TW90-CD	TW90 Counter Display (6 per display)	1 display
TW90-STK	Floor Stack Display, 24 TW90	1 display
TWMXD-FD	Mixed Floor Display, 24 TW40 & 6 TW90	1 display
TW01-CS	Clip Strips 2 strips with 6 boxes of 10 pouches in each	1 display
TW01-GR	Gravity Feed Box 100 foil pouches	1 display



TW40

TW90



TW90-CD



TW40-CD



TW01-GR



TWMXD-FD



TW90-STK



## Cable Ties White

CT04	4" White Cable Ties, 18 Tensile Strength, 100 per bag	10 bags
CT06	6"	10 bags
CT08-18	8"	10 bags

CT05	5" White Cable Ties, 40 Tensile Strength, 100 per bag	10 bags
CT08	8"	10 bags
CT07	7" White Cable Ties, 50 Tensile Strength, 100 per bag	10 bags
CT11	11"	10 bags
CT14	14"	10 bags
CT17	17"	10 bags

CT08-120	8" White Cable Ties, 120 Tensile Strength, 100 per bag	10 bags
CT14-120	14"	10 bags
CT18	18"	10 bags
CT24	24" White Cable Ties, 175 tensile Strength, 50 per bag	5 bags
CT36	36"	5 bags
CT48	48"	5 bags



## Cable Ties Black

CB04	4" Black Cable Ties, 18 Tensile Strength, 100 per bag	10 bags
CB06	6"	10 bags
CB08-18	8"	10 bags

CB05	5" Black Cable Ties, 40 Tensile Strength, 100 per bag	10 bags
CB08	8"	10 bags
CB07	7" Black Cable Ties, 50 Tensile Strength, 100 per bag	10 bags
CB11	11"	10 bags
CB14	14"	10 bags
CB17	17"	10 bags

CB08-120	8" Black Cable Ties, 120 Tensile Strength, 100 per bag	10 bags
CB14-120	14"	10 bags
CB18	18"	10 bags
CB24	24" Black Cable Ties, 175 tensile Strength, 50 per bag	5 bags
CB30	30"	5 bags
CB36	36"	5 bags
CB48	48"	5 bags